Influence of Hydrogen Charging on the Formation of Nanostructural Titania by Anodizing with Cathodic

Pretreatment

李勝揚;鄭信忠 Cheng H-C;Lee S-Y;Chen C-C;Shyng Y-C;Ou K-L

Abstract

The purpose of the present study was to evaluate the influences of titanium hydride on the formation of nanostructural titanium oxide by electrochemical treatment. The physico-chemical surface properties were investigated by scanning electron microscopy, cross-sectional transmission electron microscopy, thin film X-ray diffractometry, and X-ray photoelectron spectroscopy. Nano-porous structures were formed after anodization with cathodic pretreatments. The titanium hydride is formed by cathodic pre-treatments. Titanium hydride was a sacrificial layer on titanium following anodization. The sacrificial layer has a gamma-TiH_2 phase. The gamma-TiH $_2$ is a tetragonal nanostructure and its lattice constant is a = 3.12 nm. Furthermore, it was formed within titanium matrices during cathodization. The nanostructural gamma-TiH_2 decomposes after anodization. Furthermore, the nanoporous Ti formed by dissolution of TiH_2 was changed to nanoporous TiO_2. The TiH_2 plays an important role in forming nanoporous TiO_2. The triangle-like gamma-TiH_2 was observed on the Ti matrix and grain boundary. In the gamma-Ti matrix, an gamma-Ti - > gamma-TiH_2 transition occurred during cathodization. The anodization with cathodic pretreatment not only produces titanium hydride layer, but also results in formation of nanostructural titanium oxide. Nanoporous titania can be enhanced osseointegration of implant such as orthopedic and dental implants.